

SENIORS LEAGUE 2024



Oil Pattern Distance 45 Reverse Brush Drop 45 Oil Per Board Multi ul Forward Oil Total 10.985 mL Reverse Oil Total 14.3 mL Volume Oil Total 25.285 mL **Tank Configuration** Tank A Conditioner Tank B Conditioner **BOnly** IŒ **FIRE**

| 7 2L 2R 0 50 26 B 0 26.0 36.0 10.0 0 | | START | STOP | LOADS | MICS | SPEED | TANK | CROSSED | START | END | FEET | T.OIL |
|--|---|-------|------|-------|------|-------|------|---------|-------|------|------|-------|
| 3 13L 13R 2 50 18 B 30 5.8 10.9 5.1 1500 4 14L 14R 2 55 18 B 26 10.9 16.0 5.1 1430 5 15L 15R 2 50 18 B 22 16.0 21.1 5.1 1100 6 2L 2R 0 50 18 B 0 21.1 26.0 4.9 0 7 2L 2R 0 50 26 B 0 26.0 36.0 10.0 0 | 1 | 2L | 2R | 3 | 55 | 14 | В | 111 | 0.0 | 3.9 | 3.9 | 6105 |
| 4 14L 14R 2 55 18 B 26 10.9 16.0 5.1 1430 5 15L 15R 2 50 18 B 22 16.0 21.1 5.1 1100 6 2L 2R 0 50 18 B 0 21.1 26.0 4.9 0 7 2L 2R 0 50 26 B 0 26.0 36.0 10.0 0 | 2 | 12L | 12R | 1 | 50 | 14 | В | 17 | 3.9 | 5.8 | 1.9 | 850 |
| 5 15L 15R 2 50 18 B 22 16.0 21.1 5.1 1100 6 2L 2R 0 50 18 B 0 21.1 26.0 4.9 0 7 2L 2R 0 50 26 B 0 26.0 36.0 10.0 0 | 3 | 13L | 13R | 2 | 50 | 18 | В | 30 | 5.8 | 10.9 | 5.1 | 1500 |
| 6 2L 2R 0 50 18 B 0 21.1 26.0 4.9 0 7 2L 2R 0 50 26 B 0 26.0 36.0 10.0 0 | 4 | 14L | 14R | 2 | 55 | 18 | В | 26 | 10.9 | 16.0 | 5.1 | 1430 |
| 7 2L 2R 0 50 26 B 0 26.0 36.0 10.0 0 | 5 | 15L | 15R | 2 | 50 | 18 | В | 22 | 16.0 | 21.1 | 5.1 | 1100 |
| | 6 | 2L | 2R | 0 | 50 | 18 | В | 0 | 21.1 | 26.0 | 4.9 | 0 |
| 8 2L 2R 0 50 30 B 0 36.0 45.0 9.0 0 | 7 | 2L | 2R | 0 | 50 | 26 | В | 0 | 26.0 | 36.0 | 10.0 | 0 |
| | 8 | 2L | 2R | 0 | 50 | 30 | В | 0 | 36.0 | 45.0 | 9.0 | 0 |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |
| | | | | | | | | | | | | |

| | START | STOP | LOADS | MICS | SPEED | TANK | CROSSED | START | END | FEET | T.OIL |
|---|-------|------|-------|------|-------|------|---------|-------|------|------|-------|
| 1 | 2L | 2R | 0 | 50 | 30 | В | 0 | 45.0 | 36.0 | -9.0 | 0 |
| 2 | 14L | 14R | 2 | 55 | 22 | В | 26 | 36.0 | 29.8 | -6.2 | 1430 |
| 3 | 13L | 13R | 2 | 55 | 18 | В | 30 | 29.8 | 24.7 | -5.1 | 1650 |
| 4 | 12L | 12R | 2 | 55 | 18 | В | 34 | 24.7 | 19.6 | -5.1 | 1870 |
| 5 | 11L | 11R | 2 | 55 | 14 | В | 38 | 19.6 | 15.7 | -3.9 | 2090 |
| 6 | 10L | 10R | 1 | 55 | 14 | В | 21 | 15.7 | 13.8 | -1.9 | 1155 |
| 7 | 2L | 2R | 3 | 55 | 14 | В | 111 | 13.8 | 7.9 | -5.9 | 6105 |
| 8 | 2L | 2R | 0 | 50 | 14 | В | 0 | 7.9 | 0.0 | -7.9 | 0 |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

Geaner Ratio Main Mix
Geaner Ratio Back End Mix
Geaner Ratio Back End Distance

NA NA NA Forward Reverse

Combined

Buffer RPM: $4 = 700 \mid 3 = 500 \mid 2 = 200 \mid 1 = 100$

ROUTE 66 - 4345 As one the longest roads in America , so is this pattern in the series. At 45 feet in length, a nd as with most long oil patterns, the optimum line is usually one that is closer to the pocket or more towards the inside por tion of the lane. The greatest slope of conditioner on the ROUT E66 is from the 11th board to the 16th board so players should

| Item | 3L-7L:18L-18R | 8L-12L:18L-18R | 13L-17L:18L-18R | 18L-18R:17R-13R | 18L-18R:12R-8R | 18L-18R:7R-3R |
|------------------|----------------|----------------|-----------------|-----------------|----------------|----------------|
| Description | Outside:Middle | Middle:Middle | Inside:Middle | MIddle: Inside | Middle:Middle | Middle:Outside |
| Track Zone Ratio | 3.59 | 2.7 | 1.08 | 1.08 | 2.7 | 3.59 |



